

**M&D ELEKTRO**

Kabelová vývodka s Pg závitem

Technické parametry

Materiál: Polyamid PA6 V-2
Barva: RAL 9005(černá)
RAL 7035(světle šedá)
Krytí: **IP 68 – 5barů**
Prac. teplota: stálá -20°C až 100°C

Kabelová vývodka Pg

Velikost	Upínací rozsah	Velikost klíče	Délka závitu	Baleno kusy	Typ Objednací číslo	Cena v Kč/ks
Pg7	3 - 6,5	15	8	100	50.007 PA7035	4,60
Pg9	4 - 8	19	8	100	50.009 PA7035	4,70
Pg11	5 - 10	22	8	100	50.011 PA7035	5,60
Pg13,5	6 - 12	24	9	100	50.013 PA7035	6,10
Pg16	10 - 14	27	10	50	50.016 PA7035	7,10
Pg21	13 - 18	33	11	50	50.021 PA7035	10,70
Pg29	18 - 25	42	11	25	50.029 PA7035	21,40
Pg36	22 - 32	53	13	10	50.036 PA7035	39,70
Pg42	30 - 38	60	13	5	50.042 PA7035	51,60
Pg48	34 - 44	65	14	5	50.048 PA7035	64,30



Matice pro vývodku Pg

Velikost	Upínací Rozsah	Délka závitu	Baleno kusy	Typ Objednací číslo	Cena v Kč/ks
Pg7	19	5	100	207 PA7035	0,90
Pg9	22	5	100	209 PA7035	0,90
Pg11	24	5	100	211 PA7035	0,90
Pg13,5	27	6	100	213 PA7035	1,10
Pg16	30	6	100	216 PA7035	1,20
Pg21	36	7	100	221 PA7035	1,70
Pg29	46	7	100	229 PA7035	2,90
Pg36	60	8	50	236 PA7035	4,90
Pg42	65	8	50	242 PA7035	9,60
Pg48	70	8	50	248 PA7035	14,40